

monitor Lifts

125 Series

125 Series Monitor Lifts



With the self propelled Monitor Lift 125 series access platforms you can reach places where many other lifts cannot go. Full time four wheel drive makes driving easy even in difficult conditions and on uneven terrain. With the Monitor you can also work indoors and in similar tight situations - features that make the Monitor 125 more versatile than most other lifts. Monitor 125 combines the advantages of articulating and telescopic boom design. Articulating boom construction together with telescoping upper boom give excellent up-and-over capabilities. All functions - drive, outrigger set up and boom movements - can be operated on the platform.

Despite its compact dimensions the Monitor 125 offers features you haven't seen before. Efficiency, stability, safety and quality are on a level that is usually associated with much more expensive larger equipment.

Monitor Lift 125 series platforms can be operated from a trailer specially made for the 125 series - you just drive the lift on the trailer and start to work : very fast and efficient. Total weight of the Monitor 125 with trailer is 1.600 kg.

It can be really difficult to drive an ordinary access platform in through the door. The Monitor 125 can go through a 100 cm doorway - min. overall width with narrow tyres is 95 cm only. In addition, the Monitor 125 turns 360 degrees on the spot.



With the front jockey wheel that lifts the front wheels off the ground the Monitor 125 can work on sensitive areas like marble or timber flooring without leaving tracks on the floor.

Technical Features

STANDARD FEATURES INCLUDE

- 4WD
- Hydraulic Telescope
- Honda 13 Hp petrol engine, electric start.
- Hydraulic outriggers.
- Hour meter.
- SetUp outrigger control.
- CE certification.

AVAILABLE OPTIONS

- 230 V (110 V) at platform
- Dual power petrol or diesel/ 230 V (110 V)
- Kubota 9.5 Hp diesel engine.
- Water hose to platform.
- High pressure hose to platform.
- Larger platform.
- Special painting.
- Green plastic pads
- Hydraulic high pressure washer
- Jockey wheel.
- Load control

SPECIFICATIONS

Maximum Working Height.....	12.5m
Maximum Platform Height	10.5m
Maximum Horizontal Reach	6.3m
Safe Working Load	135/200*kg
Transport Length with Platform.....	5.0m
Transport Length without Platform.....	4.4m
Overall Height.....	1.8m
Overall Width	
Normal Tyres	1.03m
Narrow Tyres	0.95m
Rubber Tracks	1.12m
Platform Size	0.87x0.65m
Boom Slewing.....	357°
Gradeability	35%
Outrigger Spread Working.....	3.0x3.2m
Maximum Slope for Outriggers.....	25%
Weight	1300kg
Hydraulic Outriggers.....	Standard
Drive	4WD
Powered by.....	Honda 1.3 Hp petrol
Battery Type.....	1 x 43Ah Starting
Battery Charger	Automatic

*With load control

