

SL80 PALLET LIGHT

MORRIS
SITE MACHINERY

Developed to provide the market with a static eight-metre mast lighting tower and Perkins 403D-07G engine, the SL80 Pallet represents a highly transportable and compact new option, enabling 22 units to be loaded onto a Euro trailer. The model is designed to allow multiple specification options to bring real flexibility and customisation to the sector. With 246 hours running time and four 320W LEDs delivering over 130,000 lumens, the SL80 Pallet can also be fitted with the Halo lamp head.

Designed with end user ease in mind, there is no need to open any panels to deploy stability legs through its clever design.



BUILT TO PERFORM

SPECIFICATION	
ENGINE TYPE	Perkins 403D-07G @ 1500rpm
HYDRAULIC SYSTEM	Bio-degradable Oil
FUEL CONSUMPTION	0.69 l/h (Lamps only)
RUNNING TIME	246hrs
LAMP SPECIFICATION	4 x 320W LED
AVERAGE SOUND PRESSURE LEVEL @ 7 METRES	61.5dB(A)
ALTERNATOR	Mecc Alte LT3 4 -pole, 230V, 50Hz
CONTINUOUS POWER / STANDBY POWER	4.1KW / 4.5KW
POWER OUTLET SOCKETS	2 x 230 Volt, 16Amp
MAST MAXIMUM HEIGHT	8100mm
MAST RAISE / LOWER TIME	12 / 18 sec
WIND SPEED	Up to 100km/h
STABILISERS	4 with heavy duty square wind down legs
BUNDING	Fully banded all fluids
DIMENSIONS FOR TRANSPORT (LxWxH)	1220mm x 1150mm x 2326mm
DIMENSIONS FULLY DEPLOYED (LxWxH)	2480mm x 2480mm x 8110mm
WEIGHT FULLY FUELLED / UNFUELLED	1050kg / 905kg
QR CODES	Standard
VISUAL LEVEL GAUGES	Standard
DEEP SEA DSE	3110

Morris Site Machinery has a continuous improvement policy and therefore reserve the right to change the specification without prior notice



Features:



Super silent operation



per truck



355° mast rotation

Applications



Specifications are subject to change without prior notice