SL80 PALLET LIGHT





SL80 PALLET LIGHT



SPECIFICATION	
ENGINE TYPE	Perkins 403D-07G @ 1500rpm
HYDRAULIC SYSTEM	Bio-degradable Oil
FUEL CONSUMPTION	0.69 l/h (Lamps only)
RUNNING TIME	246hrs
LAMP SPECIFICATION	4 x 320W LED
AVERAGE SOUND PRESSURE LEVEL @ 7 METRES	61.5dB(A)
ALTERNATOR	Mecc Alte LT3 4 -pole, 230V, 50Hz
CONTINUOUS POWER / STANDBY POWER	4.1KW / 4.5KW
POWER OUTLET SOCKETS	2 x 230 Volt, 16Amp
MAST MAXIMUM HEIGHT	8100mm
MAST RAISE / LOWER TIME	12 / 18 sec
WIND SPEED	Up to 100km/h
STABILISERS	4 with heavy duty square wind down legs
BUNDING	Fully bunded all fluids
DIMENSIONS FOR TRANSPORT (LxWxH)	1220mm x 1150mm x 2326mm
DIMENSIONS FULLY DEPLOYED (LxWxH)	2480mm x 2480mm x 8110mm
WEIGHT FULLY FUELLED / UNFUELLED	1050kg / 905kg
QR CODES	Standard
VISUAL LEVEL GAUGES	Standard
DEEP SEA DSE	3110

Morris Site Machinery has a continuous improvement policy and therefore reserve the right to change the specification without prior notice



Super silent operation





Applications

























Specifications are subject to change without prior notice

